

## Super-Safe Mat

Super-Safe Matting clings to flooring with a series of aggressive, regularly spaced suction cups, providing extreme security in wet or slippery environments. It is also infused with an anti-microbial additive for protection against bacterial growth. Super Safe Mats come in 2 profiles : [Super Safe Ergo](#) and [Super Safe Smooth](#).



Super Safe Mats




ERGONOMIC



BEVELED EDGE



ISO CLEANROOM CERTIFIED



AUTOCLAVABLE



ANTIMICROBIAL

2 Profiles

Super Safe Ergo

Super Safe Smooth



## BENEFITS

**ERGONOMIC** : Designed to stimulate circulation in feet, legs and lower back. Circulation is stimulated by the unique, patented surface profile of Ergomat mats, which forces muscular response.

**BEVELED EDGES** : Always molded w/ bevels. Bevels will never curl up, eliminating trip hazards.

**AUTOCLAVABLE** : Only in size 2'x3' (60 x 90cm). Can be autoclaved in most machines.

**ANTI-MICROBIAL** : Super Safe mats are infused with an anti-microbial additive to inhibit bacterial growth and mold.

**SILICON FREE**: All Ergomat mats are silicon & latex free.

**TRUE WARRANTY** : Ergomat stands 100% behind our products with full replacement coverage if our product fails to perform as promoted within that period. At Ergomat we call this a **True Warranty**.

[www.ergomat.com](http://www.ergomat.com) - [info@ergomat.com](mailto:info@ergomat.com)

North & South America: +1-440-282-4651 | English (EU): +44 3308 280 084 | Danish: +45 702 21 840 | Dutch: +31 73 61 30 530 | Swedish: +46 42 16 36 00  
German: +49 9524 30 367-50 | French: +33 1 446 410 28

Rev. 10/13/2023

# ERGOMAT SUPER-SAFE

	SUPER-SAFE ERGO	SUPER-SAFE SMOOTH
Material .....	EPDM (Ethylene Propylene Diene Monomer rubber)	
Anti-Microbial Agent .....	Biocera A	
Color .....	Green	
Weight .....	3500 g +/- 50 g // 7.7 lbs +/- 1.75 oz	Blue: 3500 g +/- 50 g // 7.7 lbs +/- 1.75 oz Green: 3,06 kg // 6 lb 12 oz
Size .....	60 x 90 cm // 2 ft x 3 ft	Blue: 40,6 x 81,2 cm // 16 in x 32 in Green: 40,6 x 81,2 cm // 16 in x 32 in
Back Side Suction Cup Circ.....	22 mm // 0.87 in	
Suction Cup / 60 x90 cm or 2ft x 3ft .....	64	
Thermal Properties		
Minimum use .....	-40°C // -40°F	
Maximum use .....	120°C // 248°F	
UV-Resistance .....	GOOD	
Warranty .....	3 Years	

## Resistancy Chart

Outside .....	GOOD
Mineral Oils .....	BAD
Vegetable Oils .....	Depending on concentration
Coolants .....	BAD
Bases	
pH: 7- 9,5 .....	GOOD
pH: 9,5-14 .....	GOOD
ACID	
pH: 2-7 .....	GOOD
pH: 1-2 .....	GOOD
pH: < 1 .....	BAD
Alcohol .....	GOOD
Disinfectant Liquids .....	GOOD (depending on concentration)
Thinners .....	BAD
Water and Chlorine .....	Good
Halogenated Organic .....	BAD
Softeners .....	BAD
Acetates and Aldehydes .....	Depending
Acetone .....	GOOD

This chart is based on regular and prolonged exposures to the chemicals and liquids listed.

A rating of "Depending" indicates that the performance of this mat will depend on specific chemical exposures and concentrations.

A "BAD" rating is based on continuous and prolonged exposures to the listed chemicals. In situations where possible exposures are infrequent, limited in volume, and are immediately cleaned up, the resistance of the mat in this environment would likely be acceptable.

When in doubt, please contact Ergomat at [info@ergomat.com](mailto:info@ergomat.com).

[www.ergomat.com](http://www.ergomat.com) - [info@ergomat.com](mailto:info@ergomat.com)

North & South America: +1-440-282-4651 | English (EU): +44 3308 280 084 | Danish: +45 702 21 840 | Dutch: +31 73 61 30 530 | Swedish: +46 42 16 36 00  
 German: +49 9524 30 367-50 | French: +33 1 446 410 28

Rev. 10/13/2023